

X-2000SD

REEL-TO-REEL, CARTRIDGE, CASSETTE,
COMBINATION STEREO TAPE RECORDER



TWO IC MAIN PLUS TWO IC PREAMPLIFIER; TRANSFER FROM REEL TO CARTRIDGE OR CASSETTE; OUTPUT POWER: TOTAL 24W; HEADS: Reel: cross-field head; Cartridge and Cassette: one micron gap heads.

Dimensions: 13.8"(W) × 18.3"(H) × 10.6"(D) (350 × 465 × 270mm) Weight: 49.4lbs. (22.4kg)

REEL-TO-REEL

4-track stereo/monaural recording/playback

Tape Speed: 1-7/8, 3-3/4 and 7-1/2 ips (15 ips w/adapter)

Wow/Flutter: Less than 0.09% RMS at 7-1/2 ips

Frequency Response: 30 to 20,000 Hz (± 3 dB) at 7-1/2 ips

S/N Ratio: Better than 50 dB

CARTRIDGE

8-track stereo recording/playback, one hour continuous performance

Tape Speed: 3-3/4 ips

Wow/Flutter: Less than 0.20% RMS

Frequency Response: 30 to 18,000 Hz (± 3 dB)

S/N Ratio: Better than 45 dB

CASSETTE

4-track stereo recording/playback, one hour continuous performance

Tape Speed: 1-7/8 ips

Wow/Flutter: Less than 0.22% RMS

Frequency Response: 30 to 16,000 Hz (± 3 dB)

S/N Ratio: Better than 45 dB